
Maintenance Guidelines

PF101 Casper® Cloaking Technology

DESIGNTEX

Finish **None**
Cleaning Code **Water-based/Solvent (WS), Bleach (10:1)**

The following are cleaning and maintenance instructions for all Casper installations.

Post these instructions where employees and/or maintenance personnel can read them; failure to follow these instructions could damage the material and will irrevocably void your warranty.

Do not clean until thirty (30) days after the installation date.

This will ensure proper care of the adhesive and edge seal used to bond the material to the glass surface.

Cleaning Instructions

- Recommended cleaner is SimGlas® Window Film Cleaner and microfiber cloth.
- Do not use bristle brushes or any other product that might scratch the surface.
- Do not use ammonia or vinegar or any products containing ammonia or vinegar to clean the material.
- Some paper towels are coarse enough to scratch the material. Repeated use of improper cleaning implements and/or solutions will damage the appearance of the material.
- Do not use any adhesive tapes, labels, or signage on the surfaces to which the film has been applied.

Normal Viewing Conditions

View treated windows from a distance of six feet at angles of up to 45 degrees. Since a particle-free application is possible only under sterile conditions, there may be small amounts of dust or grit caught between the film and glass.

For help on specific questions relating to Casper, email casper@decorativefilm.com or casper@designtex.com.